



## PRODUCT DETAILS

250L Polyethalene Lifting Pump Station with single free standing plumbing, pump and high level alarm

- 250L Pump Station
- PE walkover lid (Class A)
- DN100 invert seal
- Combination ball/swing check valve
- Camlock to pump and discharge manifold with flexible hose
- 6mm stainless steel lifting chain and 6mm stainless steel dee shackles
- 2" tank discharge fitted
- BIA-B45VAS2 Vortex Pump
- NXT iALARM high-level alarm

## APPLICATIONS

- Able to handle liquids such as storm water, trade waste, effluence and sewage
- For pumping sewage from below the main
- Granny flats and house extensions
- Garbage rooms and boat sheds
- Small pump-away applications
- Basement pump-away

## ALARM DATA

- High-level Alarm
- Audible and visual alarm indicator
- Continuous or intermittent alarm mode




<b>RATED VOLTAGE</b>	220 - 240V 1Ph 50 Hz
<b>RATED CURRENT</b>	<1A
<b>POWER CABLE</b>	1.5m H05 Neoprene
<b>FLOAT CABLE</b>	10m H05 Neoprene
<b>FLOAT VOLTAGE</b>	24V
<b>INGRESS RATING</b>	I.P. 54
<b>OPERATING TEMP</b>	-25 deg C - +55 deg C
<b>DIMENSIONS</b>	345mm x 140mm x 305mm
<b>GROSS WEIGHT (KG)</b>	1.85kg with float and counterweight


The NXT iAlarm has no external communication function, does not control the pump or operate external alarms.

## PUMP PERFORMANCE

<b>RATED VOLTAGE</b>	220 - 240V 1Ph 50 Hz
<b>RATED CURRENT</b>	3.7A
<b>P2 POWER</b>	0.45kW
<b>POWER CABLE</b>	10m H07RNF 10 amp 3 pin plug
<b>AUTOMATIC</b>	Yes - Float switch
<b>MAX HEAD</b>	8.5 M
<b>MAX FLOW</b>	200 l/min
<b>OUTLET</b>	2" BSPF
<b>GROSS WEIGHT</b>	19.3kg



## TANK DIMENSIONS



## WARRANTY / CERTIFICATIONS



Pump



Tank

