



Submersible vortex drainage pump fitted with cast iron semi vortex impeller. Can pump particles up to 15mm.

Pump Characteristics:

- Cast iron pump body and impeller for durability
- Fully automatic operation by means of float switch.
- Triple seal system: Dual Mechanical Seal (carbon/ceramic) and oil seal
- Handy carry handle
- Hose tail adaptor included
- 240V single phase motor with built-in thermal overload protection
- 10m of power cable, H07RN-F.
- For use with clean or slightly dirty water, dewatering of cellars, storm-water pit emptying, dirty water with non-abrasive solids (up to 15mm dia.) and stringy material in suspension.
- Max Flow 150 L/min
- Max head 7.5 m

Liquid:

Liquid water temperature range: 2 – 35 °C

Materials:

Pump body: Cast Iron

Impeller: Cast iron/Nylon

Shaft: Stainless Steel

Shaft seal: Dual mechanical seal - carbon/ceramic and oils seal

Installation:

Maximum ambient temperature: 40 °C

Pipe connections discharge: 1 1/4"

Electrical data:

Rated voltage:	240V
Mains frequency:	50 Hz
Rated output:	250W
Current:	1.8 amps
Capacitor:	9 uF
Motor duty:	Continuous
Motor type:	Asynchronous
Motor protection:	Built-in thermal overload
Ingress protection:	IP 68
Insulation class:	B
Power cable length:	10 m H07RNF
Net weight:	10 kg

2 Year Bianco Pumpz Warranty

