



Submersible drainage pump fitted with cast iron semi vortex impeller.

Can pump particles up to 25mm.

Pump Characteristics:

- Cast iron pump body and impeller for durability
- Fully automatic operation by means of float switch
- Triple seal system: Dual mechanical seal - carbon/ceramic, and oil seal
- Handy carry handle
- Hose tail adaptor included
- 240V single phase motor with built-in thermal overload protection.
- 10m power cable, H07RN-F.
- For use with clean or slightly dirty water, dewatering cellars, storm-water pit emptying, dirty water with non-abrasive solids (up to 25mm dia) and stringy material in suspension.
- Max flow 300 L/min
- Max Head 10 m

Liquid:

Clean water temperature range: 2 – 35 °C

Materials:

- Pump body: Cast Iron
- Impeller: Cast iron
- Shaft: Stainless Steel
- Shaft seal: Dual mechanical seal - carbon/ceramic and oil seal

Installation:

- Maximum ambient temperature: 40 °C
- Pipe connections discharge: 2"

Electrical data:

Rated voltage:	240V
Mains frequency:	50 Hz
Rated output:	750W
Current:	5.3 amps
Capacitor:	20 uF
Motor duty:	Continuous
Motor type:	Asynchronous
Motor protection:	Built-in thermal overload
Ingress protection:	IP 68
Insulation class:	B
Power cable length:	10 m H07RNF
Net weight:	21 kg

2 Year Bianco Pumpz Warranty

