



This is a pump used for domestic hot water circulating. The Stainless steel housing makes it suitable for underfloor heating. It is maintenance free and is low in noise. Comes complete with 1-1/4" F x 3/4" F unions.

The pump is characterised by -

- Circulation body materials suitable for potable water
- 3 speed operation
- Flows to 42 l/min
- Heads to 6m

Liquid temperature: 2°C - 110°C
 Materials: Pump body: Stainless Steel 304 SS
 Impeller: Corrosion resistant composite PPO
 Back Plate and Rotor Can: Stainless Steel 304 SS
 Unions: 1-1/4" F x 3/4" F" Stainless Steel 304 SS

Installation: Maximum ambient temperature: 40°C
 Maximum Operating Pressure: 10 bar
 Port spacing: 150mm
 Port size: 1-1/4" BSPM
 (3/4" BSPF if used with supplied unions)

Electrical Data: 230V
 Mains Frequency: 50Hz
 Power consumption speeds: 1,2,3 55W 70W 100W
 Motor: Continuous
 Motor type: Canned rotor
 Ingress Protection: IP44
 Power cable: 1m

Bianco Pumpz 2 Year Warranty



Also available:
 BIA-C2580-180
 BIA-C1509-160
 BIA-ICIRC150
 BIA-C3280-180