



BIANCO VULCAN 1.6 HP PORTABLE PETROL ENGINE PUMP

The pump is a light weight self priming engine driven pump supplied ready to operate with hose fittings and suction strainer.

The pump is characterised by:

- Single Cylinder, 2 Stroke, Forced Air Cooled Engine
- Heads to 35 metres
- Flows to 100 l/min
- Suction to 8m
- 1" BSP Male Discharge Port
- 1" BSP Male Suction Port
- Carry Frame
- Rubber Mounting Feet

Features:

- Custom Built Frame
- Spark Arrester
- Full Serviceability Without Removing Pump from Frame

Applications:

- Dust Suppression
- Water Transfer
- Tank Filling
- De-watering

| Liquid: | Engine Data: |
|--|---|
| Liquid Type: Clean Water Clean water temperature range: 2 - 35° C | Type: Single Cylinder, Aircooled, 2 Stroke 25: 1 Ratio |
| Materials: | Model: G43 |
| Pump Body: Aluminium | HP gross: 1.6 |
| Impeller: Aluminium | Displacement: 42.7 cc |
| Mechanical Seal: Carbon/Ceramic/Nitrile | Air Cleaner: Dual Element, Paper and Foam |
| O rings: Nitrile | Ignition: CDI |
| Installation: | Starting: Recoil |
| Maximum ambient temperature: 40°C | Fuel Capacity: 1.0 Litre |
| Self Priming Time at 5m: <120 seconds | |
| Weight: | |
| 10kg | |

