

PRODUCT SPECIFICATION



HR TYPE P SOLVENT

Type P high strength PVC solvent cement used on all classes of PVC pressure pipe and fittings through 150mm.

SPECIFICATIONS

Clear, luminous green, viscous liquid
0.97 - 1.00 specific gravity
79.6°C boiling point
74% volatile
8°C flash point
3000 - 4000 (cPs @ 20°C) viscosity
Brush applicator attached to lid
Plastic containment
Conforms to Australian Standard AS3879

CHEMICAL ENTITY

Methyl Ethyl Ketone 20 - 40 %w/w
Cyclohexanone 20 - 40 %w/w
Gamma Butyrolactone 10 - 20 %w/w
Other ingredients which are classified as non hazardous to 100%



PRECAUTIONS FOR USE

Wear chemical resistant gloves, chemical splash goggles.
Use approved respiratory protection such as air supplied mask when used in enclosed area.
Do not use in confined spaces. Provide adequate ventilation

SAFE HANDLING

Material is dangerous when exposed to heat or flame. Keep container closed when not in use.
Do not handle or store near open flame, heat or strong oxidants. Adequate ventilation required.

MATERIAL SAFETY DATA SHEET

Please consult MSDS for complete safety data instructions available from HR Products

SIZES	CODE	BARCODE	CTN QTY	CUBIC AREA M ²	WEIGHT Kg
125ml	ATPS125	931453805316	36	0.012	6.1
250ml	ATPS250	931453805317	36	0.020	10.9
500ml	ATPS500	931453805318	20	0.022	11.6

Specifications Subject to Change Without Notice - Product Drawings / Images are representative only and are subject to change

PERTH

PH: 08 9455 1677
FAX: 08 9455 1680
hrsales@hrproducts.com.au

SYDNEY

PH: 02 9725 5733
FAX: 02 725 5283
infonsw@hrproducts.com.au

MELBOURNE

PH: 03 9457 7500
FAX: 03 9457 7400
infovic@hrproducts.com.au

BRISBANE

PH: 07 3806 0522
FAX: 07 3806 0533
infoqld@hrproducts.com.au

ADELAIDE

PH: 08 8341 0008
FAX: 08 8341 0707
infosasa@hrproducts.com.au